

## MATERIAL SAFETY DATA SHEET

### OTO-EASE®

**Date Prepared: 1/Apr/13**

Emergency/Customer Service Phone#: (800) 525-5071

#### SECTION I – IDENTITY

Description: Personal/professional (clinical) lubricant.  
Potentially Hazardous Ingredients:

1. Carbopol resin, CAS#: 9003-01-4, Exposure limits – none listed
2. Sodium Hydroxide, CAS#: 1310-73-2, OSHA PEL – 2mg/m<sup>3</sup>ACHIH TLV (ceiling – 2mg/m<sup>3</sup>).

#### SECTION II – PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance: A viscous, translucent, odorless jelly, free from foreign matter.

Specific Gravity: 1.01

Solubility: Complete in water

pH: 5.6 – 6.7

#### SECTION III – FIRE AND EXPLOSION HAZARD DATA

Condition: No fire or explosion hazard.

Extinguishing: Use standard fire fighting procedures depending on the source of the surrounding fire.

#### SECTION IV – REACTIVITY DATA

Incompatibilities: None

Hazardous Polymerization: Will not occur

Hazardous Decomposition or By-products: This product is stable.

#### SECTION V – TOXICOLOGY/HEALTH EFFECTS

Occupational exposure is not expected to produce adverse human health effects following normal workplace practices. Product has very low acute toxicity. There are no known chronic health effects. Direct eye contact may cause temporary discomfort with mild redness.

#### SECTION VI – FIRST AID

Route of Entry: Accidental ingestion is possible.

Emergency and First Aid Procedures: In case of eye contact, flush eyes with plenty of 1% physiological saline solution. If no saline is available, flush with plenty of water.

#### SECTION VII – PRECAUTIONS FOR SAFE HANDLING

General: None

Steps to Be Taken in Case Material is Spilled: Pick up in the most efficient manner. Product can be very slippery.

Waste Disposal Method: Place material into waste receptacles and dispose of in accordance with environmental regulations.

#### SECTION VIII – CONTROL MEASURES

Personal Protective Equipment: Not required

Ventilation: None